

S50i

VoIP PBX

Yeastar S50i is designed to provide a robust small business communication solution. It comes out-of-box with full phone system features plus enhancing UC capacity with Linkus UC Clients. The easy management, abundant features, and quick provisioning empower S50i to deliver a convenient calling experience, secure communications, and allow customers meet their specific needs in various scenarios.



Specifications

Users	50
Max Concurrent Calls	20
VoIP Trunks	50
LAN / WAN	2 10/100 Mbps
Protocol	SIP (RFC3261), IAX2
Transport Protocol	UDP, TCP, TLS, SRTP
Codec	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4
DTMF	In-band, RFC4733, RFC2833, SIP INFO
IP Services	Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN
Voicemail	5000 min (expandable)
Company Contacts	500
App Center	Linkus, Auto Provisioning, LDAP Server, Conference Panel, VPN Server, Billing App*, Hotel App*, char utile h+ Integration, Zoho Integration
External Storage	SD Card
Power	AC 100-240V 50/60HZ 0.6A max
Size (L x W x H) (cm)	34 x 21 x 4.4
Weight	1.48 kg
Environment	Operation Range: 0°C to 40°C, 32°F to 104°F; Storage Range: -20°C to 65°C, -4°F to 149°F; Humidity: 10-90% non-condensing
Mounting	1U Rack-mount

Features

- Linkus UC Clients
- Linkus Cloud Service*
- Remote Management
- Mobility Extension
- Automated Attendant (IVR)
- AutoCLIP
- Attended Transfer
- SLA
- Voicemail
- Ring Group
- Blind Transfer
- Real-time Status Monitor
- Paging/Intercom
- One Touch Recording
- Queue
- Speed Dial
- Music on Hold
- User Permission
- Event Center
- Call Detail Records (CDR)
- Call Forwarding
- Call Monitor
- Call Parking
- Call Pickup
- Call Recording
- Call Routing
- Call Back
- Call Waiting
- Caller ID
- Contacts
- Do Not Disturb (DND)
- Custom Prompt
- Blocklist/Allowlist
- PIN List
- Phone Provisioning
- SIP Forking
- Time Condition
- Dial by Name
- Email to SMS/SMS to Email
- Fax to Email
- T.38 Fax
- User Portal
- DISA
- Distinctive Ringtone
- DNIS
- Firewall
- Hot Standby
- LDAP
- Multi-language System Prompt
- Multi-language System Language
- Multi-site Interconnect

* Features with the star mark are paid features.

* Telephony modules (FXS, FXO, ISDN BRI/PRI, GSM/3G/4G) are not supported on S50i.